

## JEDYNKA® JEDYNKA DECO & PROTECT ZMYWALNA

### LATEX PAINT FOR WALLS AND CEILINGS



- Intelligent surface:
  - barrier for stains and dirt
  - easy cleaning
  - high hiding power
- Paint durable to scrubbing and multiple washing acc. to norm PN-EN I 3300 – 2nd class
- Quick drying
- Painting without dripping
- Ecological recipe
- Great coverage: up to 14 m<sup>2</sup>/l per one coat

### PRODUCT DESCRIPTION

High quality washable, matt, latex paint for interior painting of walls and ceilings.

### RECOMMENDED USES

The product is intended for decorative painting of walls and ceilings inside residential buildings, public utilities: including educational and health care facilities excluding walls around washbasins, sinks and rooms requiring disinfection or aseptic maintenance of walls; service and production facilities, including the food industry without direct contact with food. The paint perfectly covers cement-lime plasters, concrete substrates, plasterboards (dry plasters). It can also be used to renovate previously painted surfaces.

### APPLICATION

#### Surface Preparation

New surfaces: should be dry, clean and free from grease. Fresh plaster or concrete can be painted after 3-4 weeks of seasoning.  
Surfaces for renovation: thoroughly clean the surface from dirt, dust it off and then wash with water. Surface of glue paint should be removed thoroughly until the plaster is exposed. Chalky surfaces should be dusted and wash with water. Walls previously painted with emulsion paints should be washed with water and detergent and then washed with clean water. Cracks and unevenness smooth with putty. Do not apply on surfaces primed with lime. All painted surfaces must be dry before application. In the case of loosely bound substrates, it is recommended to use a suitable agent for loose substrates.

#### Application Method

Apply: brush, roller or air spray.

#### Painting

Mix thoroughly before painting. It is recommended to paint 2 coats for the required parameters. For the first coat the paint can be diluted with water up to max. 40%, depending on the type of substrate and the method of painting.

#### Notice!

1. For brush or spray application paint can be diluted with a small amount of water to the required viscosity.
2. Do not add lime or chalk to the product.
3. When painting with colored paints, the following rules must be followed:
  - when painted with intensive colors do not make single corrections, but paint the entire wall, one room paint only with one painting technique,
  - to avoid differences in shades, use product from one production batch,
  - when using several cans of paint of the same color, but from different batches, they should be mix in a larger packaging.
4. Please note that the surface painted with matt paint is more susceptible to scratches and mechanical interference as compared to painted surfaces with higher gloss levels.
5. Application should be made in temperature from +5°C to +25°C.
6. Depending on the condition of the substrate (increased absorbency, porosity, intense color), more layers may be required.

### CLEANING OF EQUIPMENT

Tools clean with water immediately after painting. Wipe away excessive paint from the tools before cleaning.

### COLORS

36 ready-made shades.

## GLOSS

Matt.

## COVERAGE

Up to 14 m<sup>2</sup>/l per coat. Actual spreading rates will depend upon absorbing capacity of the substrate and application method.

## CAN SIZES

2,5 L, 5,0 L

## HEALTH AND SAFETY

The product used for its intended purpose and according to the instructions for use does not pose a health or environmental. Keep out of the reach of children. During application wear suitable working clothes and protective gloves. Closed areas should be well aired after application until the odour is gone, then they can be used. Wipe away excessive paint from the tools before cleaning. This product contains a biocidal product for the preservation of the product during storage. Contains 2-methyl-2H-isothiazol-3-one (MIT), 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. Safety Data Sheet available at Client request. Do not pour liquid waste into drains. Empty cans should be recycled or disposed of in accordance with local regulations. Empty cans as well as cans with liquid waste should be taken to a disposal according to the local regulations. For more information please contact local authority. Contains 1,2-benzisothiazol-3(2H)-one (BIT), reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)) and 2-methyl-2H-isothiazol-3-one (MIT). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: 1,2-benzisothiazol-3(2H)-one (BIT), reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)) and 2-methyl-2H-isothiazol-3-one (MIT).

## STORAGE AND TRANSPORTATION

Protect from frost and sunlight. Transport and storage in tightly closed containers in temperatures from +5°C to +25°C.

## TECHNICAL DATA

Wet scrub resistance	Acc. to norm: PN-EN 13300 - IInd class Acc. to norm: PN-C-81914:2002 – 1st type paint
Viscosity (+23°C) KU	110-125
Density (kg/l)	max. 1,40
Drying times	The paint dries about 2 hours. Subsequent layers are recommended to be applied after at least 4 hours.

## ADDITIONAL INFORMATION

Cat. A/a. Acceptable VOC content since 2010 - 30 g/l. Product contains below: 2 g/l VOC.

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.