

JEDYNKA® FASADOWA

ACRYLIC PAINT FOR FACADES AND INTERIORS



- Durable colours
- resistant to atmospheric conditions
- easy application
- Effect of unified surface, no brush smudges
- Ecological recipe
- great coverage: approx.: 8 m²/l per one coat

PRODUCT DESCRIPTION

Ecological dispersion, acrylic paint for exterior and interior application. It creates matt surfaces resistant to atmospheric conditions, gives long lasting decorative effect. Product has very good adhesion to the surface. Micro-porous coat of paint ensure micro ventilation of painted surface.

RECOMMENDED USES

Product is used for decorative and protective application on exterior cement and cement-lime plasters, as well as walls and ceilings in living quarters, office spaces and public buildings and for decorative painting of concrete surfaces.

APPLICATION

Surface Preparation

New, unpainted surfaces must be dry and thoroughly cleaned of any flaking paint, dust, grease and other dirt, which can impair adhesive power of paint. New plaster and concrete substrates can be painted after 4 weeks of seasoning (we recommend to wait with painting of new buildings after the first heating season, during this time the construction humidity will evaporate), after priming with JEDYNKA® FASADOWA thinned with water up to 30%. In case of renovation remove any flaking old paint, work chalked substrates through sandblasting and glossy surfaces matt down with sanding, then surfaces should be dusted and washed with water prior to painting. Layers of lime and glue paint have to be removed completely to uncover plaster. Uneven surfaces, cracks should be even with cement-lime filler and after that primed with thinned paint.

Application Method

Paint can be applied with brush, roller or airless spray.

Painting

Before application paint should be well stir. Product does not require thinning. It is recommended to apply 2-3 coats. It's not allowed to add to the product lime or chalk. The paint is dry after approx. 2 hours. Consecutive coats can be applied not earlier than after 4 hours. Painting should be performed at the temperature from +5°C to +25°C.

Notice! To avoid differences with shades please use paint from one production batch.

CLEANING OF EQUIPMENT

Wipe away excessive paint from the tools before cleaning. Thinner/ tools cleaning: water

COLORS

White, as a base tintible to 237 shades

GLOSS

Matt.

CAN SIZES

1,0 L, 3,0 L, 10,0 L

HEALTH AND SAFETY

Keep out of the reach of children. During application wear suitable working clothes and protective gloves. Closed areas should be well aired after application until the odour is gone, then they can be used. Wipe away excessive paint from the tools before cleaning. Empty cans as well as cans with remains of paint should be given to special point where such waste are collected. Precise information about waste disposal can be found in local municipality office. Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)), 1,2-benzisothiazol-3(2H)-one (BIT) and 2-methyl-2H-isothiazol-3-one (MIT). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains 2-methyl-2H-isothiazol-3-one (MIT), 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1)). Safety Data Sheet available at Client request. Do not pour liquid waste into drains. Empty cans should be recycled or disposed of in accordance with local regulations. Empty cans as well as cans with liquid waste should be taken to a disposal according to the local regulations. For more information please contact local authority. Contains 1,2-benzisothiazol-3(2H)-one (BIT), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)) and 2-methyl-2H-isothiazol-3-one (MIT). May produce an allergic reaction. This product contains a biocidal product for the preservation of the product during storage. Contains: 1,2-benzisothiazol-3(2H)-one (BIT), reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)) and 2-methyl-2H-isothiazol-3-one (MIT).

STORAGE AND TRANSPORTATION

Transport and storage in tightly closed containers in temperatures from +5°C to +25°C. Storage in dry and airy rooms. Notice! Protect from frost and direct sunlight.

TECHNICAL DATA

Viscosity (+23°C) KU	100-110
Density (kg/l)	approx. 1,5
Drying times	The paint dries about 2-3 hours. Subsequent layers are recommended to be applied after at least 4 hours.

ADDITIONAL INFORMATION

Cat. A/a. Acceptable VOC content since 2010 - 30 g/l. Product contains below: 30 g/l VOC.