

JEDYNKA® PERFEKCYJNA PLUS

WHITE, ANTI-REFLEX, LATEX PAINT FOR WALLS AND CEILINGS



- ✓ Anti-reflex surface - optically masking the imperfections of the surface
- ✓ Titanium technology - increased durability and better hiding power
- ✓ Minimum VOC (less than 1g/lVOC)
- ✓ Ecological recipe
- ✓ Super coverage - up to 14m²/l
- ✓ Ideal white colour effect
- ✓ Quick dry time
- ✓ Micro ventilation of the surface

PRODUCT DESCRIPTION

Anti-reflex, white, latex paint recommended for decorative and protective painting of walls and ceilings. Creates matt surfaces with long lasting decorative effect. Unique recipe ensure pure white coatings, which doesn't crack in time because of micro-porous texture which allows "breathing" of the walls.

RECOMMENDED USES

Product is used for decorative and protective painting of walls and ceilings in living quarters, office spaces, schools and health care premises; service plant and production, also in food industry without direct contact with food. It can be applied on cement-lime plasters, concrete, gypsum, chipboard and drywalls. Is also recommended for renovation of previously painted surfaces.

APPLICATION

Application Method

Before application paint should be well stir. Product does not require thinning. Paint used for basecoat can be diluted up to 20% with water. It is recommended to apply 2 coats by brush, roller or airless spray to achieve required parameters of coating. In case of renovation of white walls and ceilings without any stain or dirt 1 coat is enough. It is recommended to apply 2 coats, to achieve required parameters of coating. Consecutive coats can be applied not earlier than after 4 hours. Painting should be performed at the temperature from +5°C to +25°C.

Unpainted surfaces: should be dry, clean and degreased. New plaster and concrete substrates can be painted after 3-4 weeks of seasoning.

Previously painted surfaces: should be thoroughly cleaned of any flaking paint, dust, grease and other dirt. Paint shouldn't be applied on surfaces primed with lime milk. Walls previously painted with emulsion paint should be thoroughly washed with solution of water detergent and rinsed with clean water. Layers of glue (calcimine) paint have to be removed completely to uncover plaster.

CLEANING OF EQUIPMENT

Wipe away excessive paint from the tools before cleaning. Thinner/tools cleaning: Water.

COLORS

White.

Product has been admitted to tinting while using the appropriate tinting machines. We've made every effort to meet the highest standards set for this class of product. Due to its specification, there is a possibility of color variations in color reproduction and/or color differences between the packaging from different production batches. In order to reduce the risk of color differences between the packages, it is advisable to purchase a quantity of paint from one production batch, which allows you to paint the entire surface, without necessity of tinting more cans. In case lack of possibility to purchase sufficient quantities of paint from one production batch, before application mix together paint from cans from different production batches. The customer who decide to tint this product understands and accepts the risk of possible deviations in color reproduction.

GLOSS

Matt.

COVERAGE

Up to 14 m²/l per coat. Actual spreading rates will depend upon absorbing capacity of the substrate and application method.

CAN SIZES

3,0 L, 5,0 L, 10,0 L

HEALTH AND SAFETY

After application the room must be ventilated till all paint odour disappears, after that the room is ready to use. Do not pour liquid waste into drains. Empty cans as well as cans with liquid waste should be taken to a disposal according to the local regulations. For more information please contact local authority. Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Contains 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)). May produce an allergic reaction. Wear protective gloves. This product contains a biocidal product for the preservation of the product during storage. Contains: 1,2-benzisothiazol-3(2H)-one (BIT) and reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (C(M)IT/MIT (3:1)).

STORAGE AND TRANSPORTATION

Protect from frost and direct sunlight. Transport and storage in tightly closed containers in temperature from +5°C to +25°C.

TECHNICAL DATA

Wet scrub resistance	Paint durable for dry rubbing. Type III according to PN-C-81914:2002
Weight solid (%)	Min. 50%
Viscosity (+23°C) KU	100-110
Density (kg/l)	max. 1,5
Drying times	The paint is dry after approx. 2 hours. Consecutive coats can be applied not earlier than after 4 hours.

ADDITIONAL INFORMATION

Cat. A/a. Acceptable VOC content since 2010r. - 30 g/l. Product contains less than 1 g/l VOC.