

JEDYNKA® ROZCIĘNCZALNIK DO WYROBÓW STYRENOWANYCH I CHLOROKAUCZUKOWYCH

THINNER FOR STYRENE AND CHLORINATED RUBBER PRODUCTS



Product is used for thinning of styrene and chlorinated rubber products, for example: JEDYNKA® NEOKOR®.

PRODUCT DESCRIPTION

Mixture of aromatic thinners. It is homogeneous, clear liquid without suspension and opacity. During thinning does not change the homogeneity of the thin product.

RECOMMENDED USES

- Does not change the homogeneity of thinned product

APPLICATION

Surface Preparation

Not applicable

Painting

Thinner should be add to the product with small portions while stir constantly. The amount of the thinner depend on required viscosity of the thin product.

COLORS

Transparent

GLOSS

Not determined

CAN SIZES

0,5 L, 5,0 L

HEALTH AND SAFETY

Contains: Reaction mass of m-xylene, o-xylene, p-xylene and ethylbenzene. **NOTICE.** Flammable liquid and vapor. Harmful in contact with skin or if inhaled. Causes serious eye irritation. Causes skin irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Avoid breathing vapor. Wear protective gloves/clothing. Use only outdoors or in a well-ventilated area. Keep away from sparks and open flames. – No smoking. **IF IN EYES:** Rinse cautiously with water for several minutes. **IF ON SKIN:** Wash with plenty of soap and water. **IF SWALLOWED:** Immediately call a POISON CENTER or physician. Do NOT induce vomiting. Store locked up. Empty cans as well as cans with remains of paint should be given to special point where such waste are collected. Precise information about waste disposal can be found in local municipality office. Empty cans as well as cans with liquid waste should be taken to a disposal according to the local regulations. For more information please contact local authority. **Contains:** Reaction mass of ethylbenzene and xylene. **Danger.** Flammable liquid and vapor. May be fatal if swallowed and enters airways. Harmful in contact with skin or if inhaled. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapors/spray. Wear protective gloves/clothing. In case of inadequate ventilation wear respiratory protection. **IF SWALLOWED:** Immediately call a POISON CENTER or physician. **IF ON SKIN:** Wash with plenty of soap and water. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting.

STORAGE AND TRANSPORTATION

Transport and storage in tightly closed containers in temperatures from +5oC to +25oC. Storage in dry and well ventilated areas.

TECHNICAL DATA

Viscosity (+23°C) KU	-
Density (kg/l)	0,85-0,86
Drying times	Not determined

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.