

JEDYNKA® ROZCIEŃCZALNIK NISKOAROMATYCZNY DO WYROBÓW FTALOWYCH I ALKIDOWYCH

LOW AROMATIC THINNER FOR ALKYD AND PHTHALATE PRODUCTS



Product is used for thinning of phthalate and alkyd products.

PRODUCT DESCRIPTION

De-aromatic mixture of aliphatic thinners. It is homogeneous, clear liquid without suspension and opacity. During thinning does not change the homogeneity of the thin product. Because of the slight amount of aromatic compound does not exude sharp and unpleasant odour

RECOMMENDED USES

- Doesn't emit sharp, unpleasant smell
- Doesn't cause changes in uniformity of thinned product.

APPLICATION

Surface Preparation

Not applicable

Application Method

Not applicable

Painting

Thinner should be added to the product with small portions while stir constantly. The amount of the thinner depends on required viscosity of the thin product.

COLORS

Transparent

GLOSS

Not determined

CAN SIZES

0,5 L, 5,0 L

HEALTH AND SAFETY

After application the room must be ventilated till all paint odour disappears, after that the room is ready to use. Empty cans as well as cans with liquid waste should be taken to a disposal according to the local regulations. For more information please contact local authority. **Contains:** hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics. **Danger.** Flammable liquid and vapor. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking. If medical advice is needed, have product container or label at hand. Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. Store locked up.

STORAGE AND TRANSPORTATION

Transport and storage in tightly closed containers in temperatures from +5°C to +25°C. Storage in dry and well ventilated areas.

TECHNICAL DATA

Viscosity (+23°C) KU	-
Density (kg/l)	0,77-0,81
Drying times	Not determined

The above information is not intended to be exhaustive or complete. The information is based on laboratory tests and practical experience, and it is given to the best of our knowledge. The quality of the product is ensured by our operational system, based on the requirements of ISO 9001 and ISO 14001. As manufacturer we cannot control the conditions under which the product is being used or the many factors that have an effect on the use and application of the product. We disclaim liability for any damages caused by using the product against our instructions or for inappropriate purposes. We reserve the right to change the given information unilaterally without notice.